



Project:	
Type:	
Catalog #:	

## Model OEM-3 Oval Wet Location Emergency Unit

### HOUSING

- Injection molded, UV stabilized polycarbonate housing
- UL94V-0 flame rating
- Corrosion, Flame and Vandal resistant
- Vandal resistant latch clips ensure the integrity of the unit
- Suitable for surface, ceiling for wall mount

### ELECTRICAL

- 120V or 277V AC
- Solid state charging and switching
- Recharge circuit regulated by electronic voltage sensor
- Battery low voltage disconnect (LVD)
- Brownout protection
- Overload and short circuit protection
- AC power indicator and test switch

### OPTICAL SYSTEM

- Supplied with two 5W Halogen lamps
- Lamps can be rotated, aimed and locked on two axis for ultimate adjustability
- Vacuum metalized, specular reflector combined with high efficiency lens to maximize light output

### BATTERY

- (2) 6V 5Ah sealed lead acid batteries
- Battery will operate fixture for a minimum of 90 minutes in the event of a power outage
- Self Diagnostics are standard

### CODE COMPLIANCE

- CSA Listed for Wet Locations
- IP65 Rated
- Meets UL Requirements
- NFPA 101 Life Safety Code compliant
- NEC and OSHA compliant

### WARRANTY

- 5 year warranty


## ORDERING INFORMATION

MODEL	VOLTAGE	OPTIONS
OEM-3	120V	8WH - 8W Halogen Lamps
	277V	10WH - 10W Halogen Lamps
		12WH - 12W Halogen Lamps
		CC - Custom Color (contact factory)


MODEL	VOLTAGE	OPTIONS
_____	_____	_____



## DIMENSIONS



OEM-3	A	B	C
	17"	6.5"	4"



Specifications and dimensions subject to change without notice.